

MATERIAL SAFETY DATA SHEET

Ashland Canada Corp.

Page 001

Date Prepared: 03/03/05

Date Printed: 09/19/05

MSDS No: 315.0027081-001.004

HETRON 197 ACC

1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

Product Name: HETRON 197 ACC

Company

Ashland Canada Corp.
2620 Royal Windsor Drive
Mississauga
Ontario
L5J 4E7

Emergency Telephone Number:

1-800-ASHLAND (1-800-274-5263)
24 hours everyday

Prepared by: EH&S Mississauga
Telephone: 905-823-1800

2. COMPOSITION/INFORMATION ON INGREDIENTS

Ingredient(s)	CAS Number	% (by weight)
-----	-----	-----
STYRENE	100-42-5	29.0- 33.0

3. HAZARDS IDENTIFICATION

Potential Health Effects

Eye

Can cause eye irritation. Symptoms include stinging, tearing, redness, and swelling of eyes.

Skin

Can cause skin irritation. Prolonged or repeated contact may dry the skin. Symptoms may include redness, burning, and drying and cracking of skin, burns and other skin damage. Passage of this material into the body through the skin is possible, but it is unlikely that this would result in harmful effects during safe handling and use.

Swallowing

Swallowing small amounts of this material during normal handling is not likely to cause harmful effects. Swallowing large amounts may be harmful. This material can get into the lungs during swallowing or vomiting. This results in lung inflammation and other lung injury.

Continued on next page

MATERIAL SAFETY DATA SHEET

Ashland Canada Corp.

Page 002

Date Prepared: 03/03/05

Date Printed: 09/19/05

MSDS No: 315.0027081-001.004

HETRON 197 ACC

Inhalation

Breathing of vapor or mist is possible. Breathing aerosol and/or mist is possible when material is sprayed. Aerosol and mist may present a greater risk of injury because more material may be present in the air than from vapor alone. Breathing small amounts of this material during normal handling is not likely to cause harmful effects. Breathing large amounts may be harmful. Symptoms usually occur at air concentrations higher than the recommended exposure limits (See Section 8).

Symptoms of Exposure

Signs and symptoms of exposure to this material through breathing, swallowing, and/or passage of the material through the skin may include: metallic taste, stomach or intestinal upset (nausea, vomiting, diarrhea), irritation (nose, throat, airways), central nervous system depression (dizziness, drowsiness, weakness, fatigue, nausea, headache, unconsciousness) and other central nervous system effects, loss of coordination, confusion, liver damage.

Target Organ Effects

Overexposure to this material (or its components) has been suggested as a cause of the following effects in laboratory animals: mild, reversible kidney effects, effects on hearing, respiratory tract damage (nose, throat, and airways), testis damage, liver damage, Overexposure to this material (or its components) has been suggested as a cause of the following effects in humans: mild effects on color vision, effects on hearing, respiratory tract damage (nose, throat, and airways), central nervous system effects.

Developmental Information

This material (or a component) has been shown to cause harm to the fetus in laboratory animal studies. Harm to the fetus occurs only at exposure levels that harm the pregnant animal. The relevance of these findings to humans is uncertain.

Cancer Information

There was no increase in cancer in rats exposed to styrene by inhalation. However, there was an increase in lung cancer in styrene-exposed mice. The relevance of the mouse lung cancer to humans is uncertain. Styrene did not cause cancer in mice in studies in which the chemical was placed in the stomachs through a feeding tube, or in a study in which styrene was given by injection. Epidemiological studies do not provide a basis for concluding that styrene causes cancer. Styrene is listed as a

Continued on next page

MATERIAL SAFETY DATA SHEET

Ashland Canada Corp.

Page 003

Date Prepared: 03/03/05

Date Printed: 09/19/05

MSDS No: 315.0027081-001.004

HETRON 197 ACC

carcinogen by the International Agency for Research on Cancer (IARC).

Other Health Effects

Styrene readily reacts with low concentrations of halogens (for example, fluorine, chlorine, bromine, or iodine) to form a tear-producing substance.

Primary Route(s) of Entry

Inhalation, Skin absorption, Skin contact, Eye contact, Ingestion.

4. FIRST AID MEASURES

Eyes

If symptoms develop, immediately move individual away from exposure and into fresh air. Flush eyes gently with water for at least 15 minutes while holding eyelids apart; seek immediate medical attention.

Skin

Remove contaminated clothing. Flush exposed area with large amounts of water. If skin is damaged, seek immediate medical attention. If skin is not damaged and symptoms persist, seek medical attention. Launder clothing before reuse.

Swallowing

Seek medical attention. If individual is drowsy or unconscious, do not give anything by mouth; place individual on the left side with the head down. Contact a physician, medical facility, or poison control center for advice about whether to induce vomiting. If possible, do not leave individual unattended.

Inhalation

If symptoms develop, move individual away from exposure and into fresh air. If symptoms persist, seek medical attention. If breathing is difficult, administer oxygen. Keep person warm and quiet; seek immediate medical attention.

Continued on next page

MATERIAL SAFETY DATA SHEET

Ashland Canada Corp.

Page 004

Date Prepared: 03/03/05

Date Printed: 09/19/05

MSDS No: 315.0027081-001.004

HETRON 197 ACC

Note to Physicians

This material is an aspiration hazard. Potential danger from aspiration must be weighed against possible oral toxicity (See Section 3 - Swallowing) when deciding whether to induce vomiting. Preexisting disorders of the following organs (or organ systems) may be aggravated by exposure to this material: respiratory tract skin, lung (for example, asthma-like conditions), liver, male reproductive system, auditory system.

5. FIRE FIGHTING MEASURES

Flash Point

26.6 - 32.2 C (80.0 - 90.0 F) SETA

Explosive Limit

(for component) Lower 1.1 Upper 6.1 %

Autoignition Temperature

No data

Hazardous Products of Combustion

May form: carbon dioxide and carbon monoxide, toxic fumes, various hydrocarbons.

Fire and Explosion Hazards

Material is volatile and readily gives off vapors which may travel along the ground or be moved by ventilation and ignited by pilot lights, flames, sparks, heaters, smoking, electric motors, static discharge or other ignition sources at locations near the material handling point. Never use welding or cutting torch on or near drum (even empty) because product (even just residue) can ignite explosively. During a fire, irritating or toxic decomposition products may be generated.

Extinguishing Media

regular foam (such as AFFF), water fog, carbon dioxide, dry chemical.

Continued on next page

MATERIAL SAFETY DATA SHEET

Ashland Canada Corp.

Page 005

Date Prepared: 03/03/05

Date Printed: 09/19/05

MSDS No: 315.0027081-001.004

HETRON 197 ACC

Fire Fighting Instructions

Wear full firefighting turn-out gear (full Bunker gear), and respiratory protection (SCBA). Polymerization will take place under fire conditions. If polymerization occurs in a closed container, there is a possibility it will rupture violently. Cool storage container with water, if exposed to fire.

NFPA Rating

Not determined

NFPA 30 Classification

Flammable Liquid Class IC

6. ACCIDENTAL RELEASE MEASURES

Small Spill

Eliminate all sources of ignition such as flares, flames (including pilot lights), and electrical sparks. Absorb liquid on vermiculite, floor absorbent or other absorbent material. Persons not wearing proper personal protective equipment should be excluded from area of spill.

Large Spill

Prevent run-off to sewers, streams or other bodies of water. If run-off occurs, notify proper authorities as required, that a spill has occurred. Persons not wearing protective equipment should be excluded from area of spill until clean-up has been completed. Eliminate all ignition sources (flares, flames including pilot lights, electrical sparks).

7. HANDLING AND STORAGE

Handling

Containers of this material may be hazardous when emptied. Since emptied containers retain product residues (vapor, liquid, and/or solid), all hazard precautions given in the data sheet must be observed. Static ignition hazard can result from handling and use. Electrically bond and ground all containers, personnel and equipment before transfer or use of material. Special precautions may be necessary to dissipate static electricity for non-conductive containers. Use proper bonding and grounding during product transfer as described in National Fire Protection

Continued on next page

MATERIAL SAFETY DATA SHEET

Ashland Canada Corp.

Page 006

Date Prepared: 03/03/05

Date Printed: 09/19/05

MSDS No: 315.0027081-001.004

HETRON 197 ACC

Association document NFPA 77. Precautions during use: avoid prolonged or frequently repeated skin contact with this material. Skin contact can be minimized by wearing impervious protective gloves. As with all products of this nature, good personal hygiene is essential. Hands and other exposed areas should be washed thoroughly with soap and water after contact, especially before eating and/or smoking. Regular laundering of contaminated clothing is essential to reduce indirect skin contact with this material. Warning. Sudden release of hot organic chemical vapors or mists from process equipment operating at elevated temperature and pressure, or sudden ingress of air into vacuum equipment, may result in ignitions without the presence of obvious ignition sources. Published "autoignition" or "ignition" temperature values cannot be treated as safe operating temperatures in chemical processes without analysis of the actual process conditions. Any use of this product in elevated temperature processes should be thoroughly evaluated to establish and maintain safe operating conditions.

Storage

Store in closed containers in a dry, well-ventilated area. Do not store near extreme heat, open flame, or sources of ignition.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Eye protection

Chemical splash goggles in compliance with OSHA regulations are advised; however, OSHA regulations also permit other type safety glasses. Consult your safety representative.

Skin Protection

Wear resistant gloves (consult your safety equipment supplier). To prevent repeated or prolonged skin contact, wear impervious clothing and boots.

Respiratory Protections

If workplace exposure limit(s) of product or any component is exceeded (see exposure guidelines), a NIOSH/MSHA approved air supplied respirator is advised in absence of proper environmental control. OSHA regulations also permit other NIOSH/MSHA respirators (negative pressure type) under specified conditions (see your industrial hygienist). Engineering or administrative controls should be implemented to reduce exposure.

Continued on next page

MATERIAL SAFETY DATA SHEET

Ashland Canada Corp.

Page 007

Date Prepared: 03/03/05

Date Printed: 09/19/05

MSDS No: 315.0027081-001.004

HETRON 197 ACC

Engineering Controls

Provide sufficient mechanical (general and/or local exhaust) ventilation to maintain exposure below TLV(s).

Exposure Guidelines

§.

Component

STYRENE (100-42-5)

ACGIH TLV 20.000 ppm - TWA (Skin)

ACGIH TLV 85.000 mg/m3 - TWA (Skin)

ACGIH TLV 40.000 ppm - STEL (Skin)

ACGIH TLV 170.000 mg/m3 - STEL (Skin)

9. PHYSICAL AND CHEMICAL PROPERTIES

Boiling Point

(for component) 145.2 C (293.4 F) @ 760 mmHg

Vapor Pressure

(for component) 4.500 mmHg

Specific Vapor Density

> 1.000 @ AIR=1

Specific Gravity

> 1.000 @ 77.00 F

Liquid Density

9.700 - 10.100 lbs/gal @ 77.00 F

9.700 - 10.100 lbs/gal @ 77.00 F

Percent Volatiles

No data

Evaporation Rate

No data

Continued on next page

MATERIAL SAFETY DATA SHEET

Ashland Canada Corp.

Page 008

Date Prepared: 03/03/05

Date Printed: 09/19/05

MSDS No: 315.0027081-001.004

HETRON 197 ACC

Appearance

VISCOUS

State

LIQUID

Physical Form

HOMOGENEOUS SOLUTION

Color

AMBER

Odor

PUNGENT

pH

No data

Solubility in Water

NEGLIGIBLE

10. STABILITY AND REACTIVITY

Hazardous Polymerization

Product can undergo hazardous polymerization. Avoid exposure to excessive heat, peroxides and polymerization catalyts.

Hazardous Decomposition

May form: carbon dioxide and carbon monoxide, toxic fumes, various hydrocarbons.

Chemical Stability

Stable. Avoid heat, open flame, and prolonged storage at elevated temperatures. This material is unstable at elevated temperatures and pressures.

Incompatibility

Avoid contact with: acids, aluminum chloride, excessive heat, halogens, iron chloride, metal salts, peroxides, strong alkalis, strong oxidizing agents.

Continued on next page

MATERIAL SAFETY DATA SHEET

Ashland Canada Corp.

Page 009

Date Prepared: 03/03/05

Date Printed: 09/19/05

MSDS No: 315.0027081-001.004

HETRON 197 ACC

11. TOXICOLOGICAL INFORMATION

LD 50 and LC 50 Data

STYRENE (CAS# 100-42-5)

Oral LD50 (rat): 2650 mg/kg

Dermal LD50: Not available

Inhalation LC50 (rat, 4 hour): 2800 ppm

12. ECOLOGICAL INFORMATION

No data

13. DISPOSAL CONSIDERATION

Waste Management Information

Dispose of in accordance with all applicable local, state and federal regulations. Do not discharge effluent containing this product into lakes, streams, ponds or estuaries, oceans, or other waters unless in accordance with the requirements of a National Pollutant Discharge Elimination System (NPDES) permit, and the permitting authority has been notified in writing prior to discharge. Do not discharge effluent containing this product to sewer systems without previously notifying the local sewage treatment plant authority. For guidance, contact your State Water Board or Regional Office of the EPA. For assistance with your waste management needs - including disposal, recycling and waste stream reduction, contact Ashland Distribution Company, IC&S Environmental Services Group at 800-637-7922.

14. TRANSPORTATION INFORMATION

TDG Information

TDG Description:

RESIN SOLUTION, 3, UN1866, III

Continued on next page

MATERIAL SAFETY DATA SHEET

Ashland Canada Corp.

Page 010

Date Prepared: 03/03/05

Date Printed: 09/19/05

MSDS No: 315.0027081-001.004

HETRON 197 ACC

Container/Mode

55 GAL DRUM/TRUCK PACKAGE

NOS Component:

None

Other Transportation Information

The Transport Information may vary with the container and mode of shipment.

15. REGULATORY INFORMATION

Canada

WHMIS Classification

Class A - Compressed Gas

Does not meet criteria

Class B - Flammable & Combustible Material

B2 - Flammable and combustible material - Flammable liquid

Class C - Oxidizing Material

Does not meet criteria

Class D - Poisonous & Infectious - Division 1

Does not meet criteria

Class D - Poisonous & Infectious - Division 2

D2A - Poisonous and infectious material - Other effects - Very toxic

D2B - Poisonous and infectious material - Other effects - Toxic

Continued on next page

MATERIAL SAFETY DATA SHEET

Ashland Canada Corp.

Page 011

Date Prepared: 03/03/05

Date Printed: 09/19/05

MSDS No: 315.0027081-001.004

HETRON 197 ACC

Class E - Corrosive Material

Does not meet criteria

Class F - Dangerously Reactive Material

F - Dangerously reactive material

This product has been classified in accordance with the hazard criteria of the CPR and the MSDS contains all the information required by the CPR.

DSL (Domestic Substance List) Status

DSL (CANADA) The intentional ingredients of this product are listed.

International Regulations

Inventory Status

AICS (AUSTRALIA) The intentional ingredients of this product are NOT listed.

ECL (SOUTH KOREA) The intentional ingredients of this product are NOT listed.

EINECS (EUROPE) This product complies with the Chemical Substance Inventory requirements.

ENCS (JAPAN) The intentional ingredients of this product are NOT listed.

IECSC (CHINA) The intentional ingredients of this product are listed.

TSCA (UNITED STATES) The intentional ingredients of this product are listed.

16. OTHER INFORMATION

The information accumulated herein is believed to be accurate but is not warranted to be whether originating with the company or not. Recipients are advised to confirm in advance of need that the information is current, applicable, and suitable to their circumstances.

Last page